

Figure 1 displays 12 histograms showing the distribution of the number of non-zero elements in the vector x for different values of n (1 to 12). The x-axis represents the 'Number of non-zero elements in x ' (ranging from 0 to 12), and the y-axis represents the 'Frequency' (ranging from 0 to 10). The distributions are unimodal and shift to the right as n increases. The histograms are labeled with n values: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12.

[21] Appl. No.: 515,097

[22] Filed: Aug. 14, 1995

[51] **Int. Cl.⁶** ----- **B41M 1/18; B41M 7/00;**
B41M 1/04; B41F 23/00

[52] U.S. Cl. ----- 101/141; 101/181; 101/183;
101/424.1; 101/424.2; 101/479; 101/483;
101/491; 101/DIG. 49

[58] **Field of Search** 101/135-138,
101/141-143, 450.1, 174, 180, 181, 183,
416.1, 424.1, 424.2, 479, 491, DIG. 29,
DIG. 49, 483

[56] **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|-----------|---------|------------------------|-------------|
| 2,499,870 | 3/1950 | Luehrs | 101/138 |
| 2,988,989 | 6/1961 | Crawford | 101/152 |
| 3,072,050 | 1/1963 | Wolff | 101/DIG. 49 |
| 4,011,812 | 3/1977 | Lecha | 101/176 |
| 4,056,056 | 11/1977 | Giori | 101/152 |
| 4,180,407 | 12/1979 | Gibson et al. | 106/26 |
| 4,186,661 | 2/1980 | Vieau | 101/178 |
| 4,373,442 | 2/1983 | Dahlgren et al. | 101/207 |
| 4,373,443 | 2/1983 | Matalia et al. | 101/221 |
| 4,417,516 | 11/1983 | Fischer | 101/181 |
| 4,421,027 | 12/1983 | Fischer | 101/142 |
| 4,437,402 | 3/1984 | Fischer | 101/181 |
| 4,610,201 | 9/1986 | Jeschke | 101/DIG. 49 |
| 4,729,909 | 3/1988 | Noack | 427/288 |
| 4,758,886 | 7/1988 | Rylander | 358/80 |
| 4,796,556 | 1/1989 | Bird | 118/46 |
| 4,989,079 | 1/1991 | Ito | 358/80 |
| 4,989,080 | 1/1991 | Ito | 358/80 |
| 5,144,419 | 9/1992 | Nakatsuka et al. | 358/75 |
| 5,178,678 | 1/1993 | Koehler et al. | 118/46 |
| 5,184,556 | 2/1993 | Schaeuble | 101/483 |
| 5,370,976 | 12/1994 | Williamson et al. | 430/358 |

OTHER PUBLICATIONS

"Pontone® Metallic Integrated Process Color Selector, Pantone Metallic-Buntdruck-Farbskala", The Pantone Library of Color, 201 Pantone, Inc. 1990, pp. MIPP VI-VIII

Primary Examiner—Stephen R. Funk
Attorney, Agent, or Firm—Jones, Day, Reavis & Pogue

[57] **ABSTRACT**

A combined lithographic/flexographic printing process having a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process. One of the stations prints a first color image using the flexographic process and at least one of the successive printing stations prints a second color image over the first color image using an offset lithographic process in the continuous in-line process.

41 Claims, 1 Drawing Sheet

1
**COMBINED LITHOGRAPHIC/
FLEXOGRAPHIC PRINTING APPARATUS
AND PROCESS**

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates in general to printing machines and processes and in particular to a combined lithographic/flexographic in-line printing apparatus and process.

2. Description of Related Art

As used herein, the following terms have the meanings indicated:

ANILOX ROLLER

A steel or ceramic ink metering roller. Its surface is engraved with tiny, uniform cells that carry and deposit a thin, controlled layer of ink film or coating material onto the plate. In flexo [flexographic] presswork, anilox rollers transfer a controlled ink film from the rubber plate (or rubber-covered roller) to the web to print the image. Anilox rollers are also used in remoistenable glue units and to create "scratch-and-sniff" perfume ads.

ANILOX SYSTEM

The inking method commonly employed on flexographic presses. An elastomer-covered fountain roller supplies a controlled ink film from the ink pan to the engraved metering roller. After ink floods the metering roller, the fountain roller is squeezed or wiped usually with a doctor blade to remove the excess ink. The ink that remains on the metering roller is then transferred to the rubber printing plate.

COATER

A device with a pan to contain the coating material, a pan roller partially immersed in the coating material contained in the pan, and a coater roller to meter off a uniform film of the coating material and apply it to the printing plate.

COATING

An unbroken, clear film applied to a substrate in layers to protect and seal it, or to make it glossy.

FLEXOGRAPHIC INK

A quick-drying, fluid ink that is highly volatile or an ink that can be water based and nonvolatile.

FLEXOGRAPHY

A method of rotary letterpress printing characterized by the use of flexible, rubber, or plastic plates with raised image areas and fluid, rapid-drying inks.

HALFTONES

Dot-pattern images that have the appearance of continuous-tone images because of the limited resolving power of the human eye. This limitation accounts for an optical illusion; small halftone dots, when viewed at the normal reading distance, cannot be resolved as individual dots but blend into a continuous tone.

LITHOGRAPHIC PLATES

A lithographic plate is precoated with a light-sensitive or otherwise imageable coating, and the separation between the image and nonimage areas is maintained chemically. The image areas must be ink receptive and refuse water and the nonimage areas must be water receptive and refuse ink. The wider the difference maintained between the ink receptivity of the image areas and the water receptivity of the nonimage areas, the better the plate will be, the easier it will run on the press, and, consequently, the better the printing. There are several types of lithographic plates. The plate is an image carrier that is said to be planographic, or flat and smooth.

A printing process in which the image carrier or plate is chemically treated so that the image areas are receptive to ink.

An indirect printing method in which the inked image on a press plate is first transferred to a rubber blanket, that in turn "offsets" the inked impression to a press sheet. In offset lithography, the printing plate has been photochemically treated to produce image areas receptive to ink.

A water suspension of fibers or the suspension of pigment and adhesive used to coat papers. It may also include a suspended metallic material such as uniform-sized metal particles or nonuniform-sized metal particles.

Printing inks containing an activator that causes the polymerization of binders and solvents after exposure to a source of ultraviolet radiation.

30 When the printing plate is made, the printing image is made grease receptive and water repellant and the nonprinting areas are made water receptive and ink repellant. The plate is mounted on the plate cylinder of the press which, as it rotates, comes in contact successively with rollers wet by
35 a water or dampening solution and rollers wet by ink. The dampening solution wets the nonprinting areas of the plate and prevents the ink from wetting these areas. The ink wets the image areas which are transferred to the intermediate blanket cylinder. The inked image is transferred to the substrate as it passes between the blanket cylinder and the impression cylinder. Transferring the image from the plate to a rubber blanket before transfer to the substrate is called the offset principle.

Offset lithography has equipment for short, medium and long runs. Both sheetfed and web presses are used. Sheetfed lithography is used for printing advertising, books, catalogs, greeting cards, posters, labels, packaging, folding boxes, decalcomanias, coupons, trading stamps, and art reproductions. Many sheetfed presses can perfect (print both sides of the paper) in one pass through the press. Web offset is used for printing business forms, newspapers, preprinted newspaper inserts, advertising literature, catalogs, long-run books, encyclopedias, and magazines.

Page 4

condition that results when wet ink on the surface of the press sheets transfers or sticks to the backs of other sheets in the delivery pile.

Thus, in summary, conventional lithographic offset printing machines or presses comprise one or more image printing stations each having a printing roller or a plate cylinder to which is fastened a thin hydrophilic, oleophobic printing plate having image areas which are oleophilic and hydrophobic and background areas which are oleophobic and hydrophilic. The plate surface is continuously wetted with an aqueous damping solution which adheres only to the background areas and inked with oleo-resinous inks which adhere only to the image areas of the plate as wet ink. The ink is offset transferred to the rubber surface of a contacting blanket cylinder and then retransferred to the receptive surface of a copy web or a succession of copy sheets, such as paper, with an impression cylinder and the ink air dries by oxidation and curing after passing through a drying station.

It is also known to provide the printing machine with a downstream coating station having a blanket roller associated with a coating application unit for the application of an overall protective coating over the entire printed area of the copy sheets or web.

It is known to apply pattern coatings of protective composition by means of blanket rolls by cutting into the rubber surface of the blanket to create raised or relief surface areas which selectively receive the coating composition from the application roll for retransfer to selected areas of the copy sheets in form of pattern coatings. See U.S. Pat. No. 4,796,556.

Lithographic inks are formulated to print from planographic surfaces which use the principle that grease and water do not mix. Lithographic inks are generally very strong in color value to compensate for the lesser amount applied. They are among the strongest of all inks. The average amount of ink transferred to the paper is about half that of letter press because of the double split of the ink film between the plate cylinder and the blanket cylinder and the blanket cylinder and the substrate on the impression cylinder.

Problems occur in the offset lithographic process when attempting to print certain colors such as white and in particular white on other colors such as yellow because the color white will be faint and not sufficiently strong. In such cases, the sheet or paper or substrate requiring the white ink usually has to be run through the same printer several times before the white becomes sufficiently strong.

Further, such colors are not generally printable in an offset lithographic printing process. This means that the sheets or substrate must be removed and transferred to a second type of machine using the flexographic process to apply greater amounts of ink in successive printing runs to achieve the desired print quality.

A like situation occurs with the printing of slurry-type materials such as "scratch-and-sniff" materials which is a liquid vehicle with a slurry containing an encapsulated essence. Such liquid vehicles, because of the nature of the slurry, must be printed with a flexographic process because the anilox roller can supply greater amounts of ink to the flexo [flexographic] plate on the plate cylinder.

Again, when a liquid vehicle with a slurry having suspended material therein such as metallic particles is to be printed, an offset lithographic process cannot be used without the mixing of the aqueous solution with metallic inks which cause a dulling of the image. Further, the above-mentioned double split of the ink film adds to the dulling of the image. Therefore, to achieve desired results, the printing must take place with a flexographic printing machine.

60250-0015160

Thus, liquid opaque coatings or inks such as white colored ink, scratch-and-sniff vehicles, and slurries with metal particles do not achieve desired results when printed in an offset lithographic process and must be transferred from the offset lithographic in-line machines to a separate machine for printing in a separate run.

Such requirements not only hinder the speed of the printing process but also require additional time and thus increase the cost of the printing.

It would be advantageous to have a continuous in-line process in which not only offset lithographic printing could take place but in which, in the same in-line process, liquid printing vehicles including opaque coatings, such as white ink, and slurries containing encapsulated essences or metallic particles could also be printed and dried not only before the printing of the offset lithographic inks but also in which, after the liquid opaque coatings have been applied, an overcoating could be applied to the printed liquid vehicle image using the lithographic process in the continuous in-line process.

SUMMARY OF THE INVENTION

The present invention provides for a continuous in-line printing process having a plurality of successive printing stations for printing color images on a substrate. At least one of the stations prints a liquid vehicle image on a substrate with an opaque coating using the flexographic process and at least one of the successive printing stations printing a second color image over the liquid vehicle image on the printed substrate using the lithographic process in the continuous in-line process.

In the novel inventive system, a single in-line continuous printing process is used. One of the stations may print a liquid vehicle image on a substrate that contains a slurry with an encapsulated essence therein utilizing the flexographic process. Another one of the stations may apply an overcoating over the liquid vehicle image on the printed substrate using a lithographic process. Still another of the stations may print an aqueous-based vehicle image including a suspended metallic material therein using the flexographic process to form a metallic coating and thereafter at least one of the successive printing stations prints a color image over the aqueous-based vehicle image using the lithographic offset process in the continuous in-line process.

Whenever a station is used for flexographic printing a flexographic plate [image] is placed on the blanket cylinder for receiving the liquid vehicle and transferring the liquid vehicle to the receptive surface of the copy web or succession of copy sheets on the impression cylinder for printing. Anilox roller is associated with the flexographic plate for supplying the liquid vehicle which may be an aqueous based vehicle.

In addition, in such case, a high-velocity air dryer is associated with the impression cylinder of one or more of the printing stations where the printing on the substrate is occurring to assist in drying the ink or liquid vehicle printed on the substrate while it is on or near the impression cylinder, before the substrate arrives at the next successive station for additional printing, or before printing occurs at the next successive station.

Thus, if a liquid vehicle such as white ink is to be printed, it is printed with a flexographic process which deposits a greater amount of ink on the substrate, the ink is dried with a high-velocity air dryer while the substrate is on or near the impression cylinder and prior to the substrate being received by the next successive station. If desired, at the next successive station the printing of the white liquid vehicle may again take place thus ensuring the desired intensity of

whiteness on the substrate. Subsequently, at the next succeeding station a printing may take place on top of the white printing and such printing may continue at the remaining successive stations.

Thus, it is an object of the present invention to provide a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process and in which some of the stations print using the flexographic process and other of the stations print utilizing the offset lithographic process.

It is also an object of the present invention to print an aqueous-based vehicle image including a suspended metallic material therein using the flexographic process at one printing station and at least one successive printing station printing a color image over the aqueous-based vehicle image using a lithographic process in a continuous in-line process or placing an overcoating over the aqueous-based vehicle image using the flexographic process and then printing at successive stations using the lithographic process.

It is yet another object of the present invention to provide a continuous in-line printing process in which one of the stations prints a liquid vehicle image on the substrate with a slurry containing an encapsulated essence using the flexographic process and at least one of the successive printing stations applies an overcoating over the liquid vehicle image on the printed substrate using the offset lithographic process in a continuous in-line process.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features of the present invention will be more fully disclosed when taken in conjunction with the following DETAILED DESCRIPTION OF THE PRESENT INVENTION in which like numerals represent like elements and in which:

FIG. 1 is a schematic view of a prior art offset lithography printing station;

FIG. 2 is a generalized depiction of a printing station that may be used either as an offset lithographic station or a flexographic printing station and illustrates how the station may be converted from an offset lithographic station to a flexographic station; and

FIG. 3 illustrates the continuous in-line process of the present invention comprising a plurality of printing stations, each of which can be converted from an offset lithographic printing station to a flexographic printing station as well as a final coating station.

DETAILED DESCRIPTION OF THE PRESENT INVENTION

FIG. 1 is a schematic representation of a well-known offset lithography printing station 10 having a plate cylinder 12, a blanket cylinder 14, and an impression cylinder 16. The printing medium or substrate, such as paper 20 either in sheet form or web, is fed over the impression cylinder 16 in printing contact with the blanket cylinder 14 to receive the image and then passes over the paper transfer cylinder 18 with the image printed thereon. An inking system 26, well known in the art, transfers the ink from the ink supply to the plate cylinder 12. This is a typical offset lithography printing station.

As disclosed in U.S. Pat. No. 4,796,556, offset lithographic printing machines generally have a plurality of in-line liquid application stations at least one of which is an ink image printing station for printing lithographic ink images on to suitable receptive copy sheets. The final

600000 000000

downstream liquid application station is a coating application station for printing a protective and/or aesthetic coating over selected portions of or over the entire ink-image printed surface of the copy sheets and can also be used to print metallic coatings or slurry. As stated in U.S. Pat. No. 4,796,556, two liquid application stations are shown, the latter including a coating apparatus and the first station being a conventional offset image printing station. The coating application printing station is one that can be modified to convert it either permanently or intermittently to a coating station from an offset lithographic station.

Such a station is illustrated in FIG. 2 herein. The station 30 comprises a housing 32 which includes therein a plate cylinder 34 that is fed with an ink system of rollers 36 that take ink from an ink supply 38 and transfer it to the plate cylinder 34. A blanket cylinder 40 is in ink transfer relationship with the plate cylinder 34 and the impression cylinder 42 where the image is transferred to a substrate passing between blanket cylinder 40 and impression cylinder 42 as blanket cylinder 40 rotates in the direction of arrow 52. This is a conventional offset lithographic printing station. When it is desired to convert that station into a coater station, the coater apparatus 43 has a coater head 44 including a supply of liquid coating and an anilox roller 46 that can be moved such that it can be in contact with either the blanket cylinder 40 for direct printing or the plate cylinder 34 for offset printing. In this case, the ink rollers 36 for the lithographic system are removed from engagement with the plate cylinder 34 in a well-known manner. The coater unit 43 includes a motor device 45, an arm 47, and a pivotal connection 48 that connects the coater head 44 with the remainder of the assembly.

As stated previously, the offset lithographic machine of FIG. 2 is converted as shown therein to a coater that is used only in the last stage of an in-line printing process. It has not been able to be used in stages other than the last printing station because the ink that is placed on the blanket cylinder by means of an anilox roller is still wet when it arrives at the subsequent stations, thus causing smearing of the printed material and causing a general impossibility of printing other information thereon. However, applicant has modified the station shown in FIG. 2 by the addition of a high-velocity air dryer 50 that is associated with the impression cylinder 42 directly after the ink is transferred from the blanket cylinder to the substrate on the impression cylinder. Thus by using flexographic inks, or aqueous coatings which are naturally quick-drying inks, and the high-velocity air dryer 50 located at the point where the ink is applied to the substrate on the impression cylinder, the ink is sufficiently dried when it passes to the next station that further printing can take place on the printed substrate.

Thus, as shown in FIG. 3, a conventional in-line offset lithographic printing machine 52 is shown having an apparatus to feed paper into the said machine, referred to as a feeder 54, printing stations 56, 58, 60, 62, and 64 and a coating station 66. A delivery station 68 receives the printed material or substrates. Thus there are a plurality of successive printing stations 56, 58, 60, 62, and 64 for printing color images on the substrate in a continuous in-line process. Any one of the printing stations 56-64 can be modified as generally shown therein and as illustrated in FIG. 2 to print a first color image using the flexographic process. The succeeding printing stations can then print a second color image over the first color image using the lithographic process in the continuous in-line process. As illustrated in FIG. 2, the flexographic process printing station includes the blanket cylinder 40 and the impression cylinder 42. A

flexographic plate 41 on the blanket cylinder 40 has an image thereon for receiving the first color from the anilox roller 46 and transferring that first color image to the impression cylinder 42 for printing on the substrate. The high-velocity air dryer 50 thus dries the flexographic ink on the substrate and passes the substrate to the subsequent printing station. Thus in FIG. 3, station 56 may be modified as generally shown therein and as illustrated in FIG. 2 and a flexographic ink can be printed thereon at station 56, dried by the high-velocity air dryer 50, and coupled to subsequent in-line stations 58-64 for further printing a second or more color images over the first color image using the offset lithographic process in a continuous in-line process. The flexographic printing station shown in FIG. 2 may print a liquid vehicle image on the substrate with a slurry containing an encapsulated essence. At at least one of the successive printing stations 58-64 an overcoating may be applied over the liquid vehicle image on the printed substrate using the flexographic process in the continuous in-line process. The overcoating may be an aqueous overcoating, or an ultraviolet overcoating. In addition, the substrate may be a sheet or a web 20 as illustrated in FIG. 1 or it may be single sheet fed in the continuous in-line process from the stack sheets shown at 54 in FIG. 3.

Further, the modified flexographic printing station 30 shown in FIG. 2, as stated previously, may be any one of the stations 56-64 in FIG. 3, and as illustrated by stations 56 and 58, and may print an aqueous-based vehicle image including a suspended metallic material therein using the flexographic process to form a metallic coating. Again, after it is dried by the high-velocity air dryer 50, it may be passed to one of the successive printing stations for printing a color image over the aqueous-based vehicle image using the offset lithographic process in the continuous in-line process. The suspended material may include uniform-sized metal particles to form the metallic coating or it may include nonuniform or multiple-sized metal particles to form the metallic coating.

The present invention is especially useful when a liquid opaque coating must be printed such as a white color ink. In that case, it may be desirable to have both stations 56 and 58 modified as shown in FIG. 3 and as illustrated in detail in FIG. 2. In such case, the anilox roller 46 at each station delivers the white ink in the same pattern to the flexographic plate 41 on the blanket cylinder 40 for transfer to the substrate on the impression cylinder 42. As the substrate passes the high-velocity drying station 50, the ink is dried and the second station may again print the same white pattern on the substrate to increase the quality of the white ink appearance after it is applied to the substrate.

Thus, the station or stations that are converted to flexographic printing stations may have an ink-providing means 46 at the printing station for applying a flexographic ink to the blanket cylinder to form the image. A substrate receives the flexographic ink image transfer from the blanket cylinder and at least one subsequent printing station in the in-line process receives the image-printed substrate and prints an additional coated ink image on the substrate on top of the flexographic ink image using offset lithography. The additional colored ink images that can be printed on top of the flexographic ink images can be conventional lithographic inks or waterless inks.

Further, the colored ink images may be printed with halftone screening processes. The flexographic ink image and the colored ink images may also be printed in solids and/or halftone printing plates in sequence and in registry in successive printing stations to produce a multicolored image on the substrate. Further, the printing apparatus may include a sheetfed press or a web press.

603249 9647569

In the present invention, at least one of the flexographic printing stations prints an image with liquid vehicle slurry containing an encapsulated essence. In another embodiment, at least one of the printing stations prints an image with a water-based liquid vehicle containing suspended particles that are either uniform or nonuniform in size. The suspended particles may be metallic particles up to substantially 16 microns in diameter.

The present invention may also use the metallic color printing process as disclosed in commonly assigned U.S. Pat. No. 5,370,976 incorporated herein by reference in its entirety.

In one aspect, the novelty of the present invention is to create a flexographic printing station that can be used at one of a plurality of printing stations in a continuous in-line process and in which, at a subsequent printing station, a lithographic process may be used to print over the liquid vehicle printed by the flexographic station.

Thus, there has been disclosed an apparatus for a combined lithographic/flexographic printing process that includes a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process and wherein one of the stations prints a first color image using the flexographic process and at least one of the successive printing stations prints a second color image over the first color image using the lithographic process in the continuous in-line process.

While the invention has been described in connection with a preferred embodiment, it is not intended to limit the scope of the invention to the particular form set forth, but, on the contrary, it is intended to cover such alternatives, modifications, and equivalents as may be included within the spirit and scope of the invention as defined by the appended claims.

We claim:

1. Apparatus for a combined lithographic/flexographic printing process comprising:
 - a substrate;
 - a plurality of successive printing stations for printing color images on the substrate in a continuous in-line process;
 - one of said stations comprising a flexographic printing station for printing a liquid vehicle image on said substrate with a slurry containing an encapsulated essence using the flexographic process;
 - at least one of said successive printing stations being a lithographic printing station; and
 - an overcoating applied over the liquid vehicle image on the printed substrate at at least one of said successive lithographic printing stations using the lithographic process in said continuous in-line process.
2. Apparatus as in claim 1 wherein said overcoating is an aqueous overcoating.
3. Apparatus as in claim 1 wherein said overcoating is an ultraviolet ink overcoating.
4. Apparatus as in claim 1 wherein:
 - said substrate is a paper sheet; and
 - said apparatus includes a sheet feeder.
5. Apparatus as in claim 1 wherein:
 - said substrate is a web; and
 - said apparatus includes a web feeder.
6. Apparatus for a combined lithographic/flexographic printing process comprising:
 - a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process;

one of said stations comprising a flexographic printing station printing an aqueous-based vehicle image using the flexographic process to form a metallic coating;

a suspended metallic material being included in said aqueous-based vehicle image; and

at least one of the successive printing stations comprising an offset lithographic printing station printing a color image over the aqueous-based vehicle image using the offset lithographic process in said continuous in-line process.

7. Apparatus as in claim 6 wherein said suspended material includes uniform-sized metal particles to form said metallic coating.

8. Apparatus as in claim 6 wherein said suspended material includes nonuniform-sized metal particles to form said metallic coating.

9. Apparatus as in claim 6 further including: said flexographic printing station including a plate cylinder having a flexographic plate thereon, a blanket cylinder, and an impression cylinder;

a flexographic plate image transferred from said plate cylinder to said blanket cylinder, said image being formed of said metallic coating, said blanket cylinder transferring said metallic coating to said impression cylinder for printing said flexographic plate image on said substrate; and

an anilox roller associated with said flexographic plate for supplying said aqueous-based vehicle containing said suspended metallic material to said flexographic plate.

10. Apparatus for creating a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process;

one of said stations comprising a flexographic printing station for printing a first color image using the flexographic process; and

at least one of the successive printing stations comprising an offset lithographic printing station for printing a second color image over the first color image using the offset lithographic process in said continuous in-line process.

11. Apparatus as in claim 10 further including:

said flexographic printing station including a plate cylinder, a blanket cylinder, and an impression cylinder;

a flexographic plate on said plate cylinder;

an anilox roller associated with said flexographic plate for supplying a first color to said flexographic plate to form said first color image; and

said blanket cylinder receiving said first color image from said plate cylinder and transferring said first color image to said impression cylinder for printing on said substrate.

12. (Amended) Apparatus for creating a combined lithographic/flexographic printing process comprising:

a substrate;

a plurality of successive printing stations for printing color images on the substrate in a continuous in-line process;

at least two successive ones of said printing stations being flexography stations and comprising:

(1) a supply of liquid coating;

(2) a plate cylinder associated with a blanket cylinder, said plate cylinder having a flexographic plate thereon;

(3) an anilox roller associated with said liquid supply coating and said plate cylinder for delivering said liquid coating to said flexographic plate to form an image for transfer to said blanket cylinder;

(4) an impression cylinder holding said substrate for receiving said liquid coating image transferred from said blanket cylinder and printing said image on said substrate[.];

said at least two flexography stations printing the same liquid coating image in sequence and in superimposed relationship; and

at least one offset lithographic printing station [for] receiving said substrate and printing over said liquid coating image.

13. Apparatus as in claim 12 wherein said liquid coating image printed on said substrate is a white color ink.

14. Apparatus as in claim 12 further including an air dryer associated with each of said impression cylinders on said flexography stations, said air dryer having sufficient air velocity for drying said liquid coating before the substrate is transferred to the successive printing station in said continuous in-line process.

15. Apparatus for a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for printing color images on a substrate in a continuous in-line process, said printing stations including both lithographic and flexographic printing stations;

a blanket cylinder at at least a first one of said flexographic printing stations;

flexographic ink-providing means at said at least first one of said flexographic printing stations for applying a flexographic ink to said blanket cylinder to form an image;

a substrate for receiving said flexographic ink image transferred from said blanket cylinder; and

at least one subsequent lithographic printing station in said in-line process for receiving said image printed substrate and printing an additional colored ink image on said substrate on top of said flexographic ink image using offset lithography.

16. Apparatus as in claim 15 further comprising:

a plate cylinder at said at least first one of said flexographic stations;

a flexographic plate on said plate cylinder for receiving and transferring said flexographic ink to said blanket cylinder; and

said flexographic ink-providing means including a flexographic ink supply and an anilox roller associated with said flexographic ink supply for transferring said flexographic ink to said flexographic plate.

17. Apparatus for a combined lithographic/flexographic printing process for printing a multicolored image comprising:

a plurality of successive printing stations for printing color on a substrate in a continuous in-line process, said printing stations including both lithographic and flexographic printing stations;

at least one of said flexographic printing stations having:

(1) a plate cylinder and a blanket cylinder, said plate cylinder including a flexographic plate having an image thereon for transferring a flexographic color ink image to said blanket cylinder;

(2) an etched anilox roller for applying a flexographic color ink to said flexographic plate on said plate cylinder;

(3) an impression cylinder in ink-transfer relationship with said blanket cylinder for transferring said flexographic color ink image from said blanket cylinder to said substrate; and

at least one of said succeeding printing stations being a lithographic printing station using offset lithography for printing additional colored ink images on top of said flexographic ink image.

18. Apparatus as in claim 17 wherein said additional colored ink images are formed with lithographic inks.

19. (Amended) Apparatus as in claim 17 wherein at least one of the said colored ink images [are] is formed with a waterless [inks] ink.

20. (Amended) Apparatus as in claim 17 further including an air dryer adjacent to said impression cylinder for drying the colored flexographic ink image transferred to said substrate before said additional colored ink images are printed thereon.

21. Apparatus as in claim 17 further including halftone printing plates for printing said colored ink images.

22. (Amended) Apparatus as in claim 17 wherein said colored flexographic ink image and said lithographic colored ink images are printed as solid colors and/or with halftone printing plates in sequence and in registry in said successive printing stations to produce said multicolored image on said substrate.

23. Apparatus as in claim 17 wherein said printing apparatus includes a sheet-fed press.

24. Apparatus as in claim 17 wherein at least one of said flexographic printing stations prints said flexographic ink image with liquid vehicle slurry containing an encapsulated essence.

25. Apparatus as in claim 17 wherein at least one of said printing stations prints said flexographic ink image with a water-based liquid vehicle containing suspended particles.

26. Apparatus as in claim 25 wherein said suspended particles are uniform in size.

27. Apparatus as in claim 25 wherein said suspended particles are nonuniform in size.

28. Apparatus as in claim 25 wherein said suspended particles are metallic particles.

29. A method of combining lithography and flexographic printing in a continuous in-line process comprising the steps of:

providing a plurality of successive lithographic/flexographic printing stations for printing colored ink images on a substrate;

printing a flexographic ink image on said substrate at at least one of said flexographic stations;

transferring said printed substrate to at least one subsequent printing station in said continuous in-line process; and

printing colored ink images [on top of] over said flexographic ink image at at least one of said subsequent lithographic printing stations with an offset lithographic process.

30. A method as in claim 29 further comprising the step of drying said flexographic ink image on said substrate with an air dryer prior to printing said colored ink images thereon.

31. A method as in claim 29 further including the step of printing a coating on top of said colored ink images at one of said plurality of subsequent printing stations.

32. A method as in claim 29 wherein said colored inks forming said colored ink images are waterless.

33. A method as in claim 29 wherein said colored inks forming said colored ink images are in a solvent-based liquid vehicle.

34. (Amended) A method as in claim 29 further including the steps of: printing a slurry on said substrate at any of said printing stations in said continuous in-line process;

using an encapsulated essence in said slurry; and

printing an overcoating [over] on top of said slurry at a subsequent printing station in said in-line process to protect said essence.

35. A method as in claim 34 further including the step of printing an aqueous-based coating over said slurry.

36. A method as in claim 34 further including the step of printing an ultraviolet coating over said slurry.

37. A method of combining offset lithography and flexographic printing in a continuous in-line process comprising the steps of:

providing a substrate;

applying a flexographic ink to a blanket cylinder in a pattern with a coating head at a first flexographic printing station;

transferring said pattern of flexographic ink from said blanket cylinder to the substrate; and

printing a waterless ink pattern over said flexographic ink pattern on said substrate at at least one subsequent offset lithographic printing station in said continuous in-line process.

38. A method of combining lithography and flexographic printing in a continuous in-line process comprising the steps of:

printing an aqueous-based vehicle image having suspended particles therein on a substrate at a first flexographic printing station;

transferring said image printed substrate to at least one additional printing station in said continuous in-line process; and

printing additional colored ink images on said printed substrate over said aqueous-based vehicle image in an offset lithographic process at said at least one additional printing station in said in-line process.

39. A method of combining lithography and flexographic printing in a continuous in-line process comprising the steps of:

(1) providing a plurality of successive printing stations for printing liquid vehicle images on a substrate in said in-line continuous process;

(2) utilizing an anilox roller to transfer a liquid ink as said liquid vehicle to a flexographic plate image at at least one of said printing stations;

(3) printing said liquid ink from said flexographic plate image to a substrate;

(4) transferring said printed substrate with said liquid ink image to a subsequent printing station in said in-line printing process;

(5) repeating steps (2)-(4) at subsequent printing stations in said in-line process to achieve a desired opacity ink image on said substrate; and

(6) printing an ink pattern over said flexographic ink image using an offset lithographic process.

40. A method as in claim 39 further including the step of additionally printing colored ink images over said liquid ink image on said substrate at subsequent ones of said printing stations in said in-line process.

41. A method as in claim 40 wherein said liquid ink is an opaque white color.

42. The apparatus of any of claims 1, 6, 10, 12, 15 and 17, wherein the substrate is printed on both sides in one pass during the continuous in-line process.

43. The method of any of claims 29, 37, 38 or 39 wherein the substrate is printed on both sides in one pass during the continuous in-line process.

44. Apparatus for a combined lithographic/flexographic printing process comprising:

a substrate;

a plurality of successive printing stations for depositing a series of images on one side of a substrate in a continuous in-line process;

one of said stations comprising a flexographic printing station for printing a liquid vehicle image on said substrate using a flexographic process; and

at least one of said successive printing stations being a lithographic printing station;

whereby said substrate is printed on top of or on the opposite side of that previously printed at at least one of said successive lithographic printing stations using the lithographic process in said continuous in-line process.

45. Apparatus as in claim 44 wherein at least one of said images at the flexographic station is a coating material.

46. Apparatus as in claim 44 wherein at least one of said images at one of the lithographic stations is an ink.

47. Apparatus as in claim 44 wherein:

said substrate is a paper sheet; and

said apparatus includes a sheet feeder.

48. Apparatus as in claim 44 wherein:

said substrate is a web; and

said apparatus includes a web feeder.

49. An apparatus for a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for depositing a series of images on a substrate in a continuous in-line process;

one of said stations comprising a flexographic printing station printing an aqueous-based vehicle on one side of the substrate using the flexographic process to form a metallic coating image;

a suspended metallic material being included in said aqueous-based vehicle; and

at least one of the successive printing stations comprising an offset lithographic printing station printing a color image on top of the aqueous-based vehicle or on the opposite side to that previously printed using the offset lithographic process in said continuous in-line process.

50. Apparatus for creating a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for depositing a series of images on a substrate in a continuous in-line process;

one of said stations comprising a flexographic printing station for printing a first color image using the flexographic process; and

at least one of the other successive printing stations comprising an offset lithographic printing station for printing a second color image on the reverse side of the substrate of the first color image using the offset lithographic process in said continuous in-line process.

51. Apparatus as in claim 49 wherein said suspended material includes nonuniform-sized metal particles to form said metallic coating.

52. Apparatus as in claim 49 further including: said flexographic printing station including a plate cylinder having a flexographic plate thereon, a blanket cylinder, and an impression cylinder;

a flexographic plate image transferred from said plate cylinder to said blanket cylinder, said image being formed of said metallic coating, said blanket cylinder transferring said metallic coating to said impression cylinder for printing said flexographic plate image on said substrate; and

an anilox roller associated with said flexographic plate for supplying said aqueous-based vehicle containing said suspended metallic material to said flexographic plate.

53. Apparatus for creating a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for depositing a series of images on a substrate in a continuous in-line process;

one of said stations comprising a flexographic printing station for printing a first color image using the flexographic process; and

at least one of the other successive printing stations comprising an offset lithographic printing station for printing a second color image on the reverse side of the substrate of the first color image using the offset lithographic process in said continuous in-line process.

54. Apparatus as in claim 53 further including:
said flexographic printing station including a plate cylinder, a blanket cylinder, and an impression cylinder;
a flexographic plate on said plate cylinder;
an anilox roller associated with said flexographic plate for supplying a first color to said flexographic plate to form said first color image; and
said blanket cylinder receiving said first color image from said plate cylinder and transferring said first color image to said impression cylinder for printing on said substrate.

55. Apparatus for creating a combined lithographic/flexographic printing process comprising:

a substrate;
a plurality of successive printing stations for depositing a series of images on a substrate in a continuous in-line process;
at least one of said printing stations being flexographic stations and comprising:

(1) a supply of liquid coating;
 (2) a plate cylinder associated with a blanket cylinder, said plate cylinder having a flexographic plate thereon;

(3) an anilox roller associated with said liquid supply coating and said plate cylinder for delivering said liquid coating to said flexographic plate to form an image for transfer to said blanket cylinder;

(4) an impression cylinder for receiving said liquid coating image transferred from said blanket cylinder and printing said image on one side of said substrate; and

at least one offset lithographic printing station for receiving said substrate and printing on top of or on the opposite side to that previously printed.

56. Apparatus as in claim 55 wherein said liquid coating image printed on said substrate is a white color ink.

57. Apparatus as in claim 56 further including an air dryer associated with each impression cylinder on each flexographic station, said air dryer having sufficient air velocity for drying said liquid coating before the substrate is transferred to the successive printing station in said continuous in-line process.

58. Apparatus for a combined lithographic/flexographic printing process comprising:

a plurality of successive printing stations for depositing a series of images on a substrate in a continuous in-line process, said printing stations including both lithographic and at least two flexographic printing stations;

a blanket cylinder at at least a first one of said flexographic printing stations;

flexographic ink-providing means at the other of said flexographic printing stations for applying a flexographic ink to said blanket cylinder to form an image on one side of a substrate;

a substrate for receiving said flexographic ink image transferred from said blanket cylinder; and

at least one subsequent lithographic printing station in said in-line process for receiving said image printed substrate and printing an additional colored ink image on said substrate on top of said flexographic ink image or the opposite side to that previously printed using offset lithography.

59. Apparatus as in claim 58 further comprising:

a plate cylinder at said at least first one of said flexographic stations;

a flexographic plate on said plate cylinder for receiving and transferring said flexographic ink to said blanket cylinder; and

said flexographic ink-providing means including a flexographic ink supply and an anilox roller associated with said flexographic ink supply for transferring said flexographic ink to said flexographic plate.

60. Apparatus for a combined lithographic/flexographic printing process for printing a multicolored image comprising:

a plurality of successive printing stations for depositing a series of images on a substrate in a continuous in-line process, said printing stations including both lithographic and flexographic printing stations;

at least one of said flexographic printing stations having:

(1) a plate cylinder and a blanket cylinder, said plate cylinder including a flexographic plate having an image thereon for transferring a flexographic color ink image to said blanket cylinder;

(2) an etched anilox roller for applying a flexographic color ink to said flexographic plate on said plate cylinder;

(3) an impression cylinder in ink-transfer relationship with said blanket cylinder for transferring said flexographic color ink image from said blanket cylinder to one side of said substrate; and

at least one of said succeeding printing stations being a lithographic printing station using offset lithography for printing additional colored ink images on top of said flexographic ink image or on the opposite side to that that previously printed.

61. Apparatus as in claim 60 wherein said additional colored ink images are formed with lithographic inks.

62. Apparatus as in claim 60 wherein at least one of said colored ink images is formed with a waterless ink.

63. Apparatus as in claim 60 further including an air dryer adjacent to said impression cylinder for drying the colored flexographic ink image transferred to said substrate before said additional colored ink images are printed thereon.

64. Apparatus as in claim 60 further including halftone printing plates for printing said colored ink images.

65. Apparatus as in claim 60 wherein said colored flexographic ink image and said lithographic colored ink images are printed as solid colors and/or with halftone printing plates in sequence and in registry in said successive printing stations to produce said multicolored image on said substrate.

66. Apparatus as in claim 60 wherein said printing apparatus includes a sheet-fed press.

67. Apparatus as in claim 60 wherein at least one of said flexographic printing stations prints said flexographic ink image with liquid vehicle slurry containing an encapsulated essence.

68. Apparatus as in claim 60 wherein at least one of said printing stations prints said flexographic ink image with a water-based liquid vehicle containing suspended particles.

69. Apparatus as in claim 68 wherein said suspended particles are uniform in size.

70. Apparatus as in claim 68 wherein said suspended particles are nonuniform in size.

71. Apparatus as in claim 68 wherein said suspended particles are metallic particles.

72. A method of combining lithography and flexographic printing in a continuous in-line process comprising the steps of:

providing a plurality of successive lithographic/ flexographic printing stations for depositing a series of images on a substrate;

printing an image as one of said thin controlled layers on one side of said substrate at at least one of said flexographic stations;

transferring said printed substrate to at least one subsequent printing station in said continuous in-line process; and

printing an image on the reverse side of said substrate having said flexographic ink image, at at least one of said other subsequent lithographic printing stations with an offset lithographic process in the continuous in-line process.

73. A method as in claim 72 further comprising the step of drying said flexographic ink image on said substrate with an air dryer prior to printing said colored ink images thereon.

74. A method as in claim 72 further including the step of printing a coating on top of said colored ink images at one of said plurality of subsequent printing stations.

75. A method as in claim 72 wherein said colored inks forming said colored ink images are waterless.

76. A method as in claim 72 wherein said colored inks forming said colored ink images are in a solvent-based liquid vehicle.

77. A method as in claim 72 further including the steps of: printing a slurry on one side of said substrate at any of said printing stations in said continuous in-line process;

using an encapsulated essence in said slurry; and

printing an ink on the reverse side of said substrate at a subsequent printing station in said in-line process.

78. A method as in claim 77 further including the step of printing an aqueous-based coating over said slurry.

79. A method as in claim 77 further including the step of printing an ultraviolet coating over said slurry.

80. A method of combining offset lithography and flexographic printing in a continuous in-line process comprising the steps of:

providing a substrate;

applying an ink or coating to a blanket cylinder in a pattern with a coating head at a flexographic printing station;

transferring said pattern of ink or coating from said blanket cylinder to one side of the substrate; and

printing a waterless ink pattern on the reverse side of said substrate at at least one subsequent offset lithographic printing station in said continuous in-line process.

81. A method of combining lithography and flexographic printing in a continuous in-line process comprising the steps of:
printing an aqueous-based vehicle having suspended particles therein on one side of a substrate at a flexographic printing station to form an image;

transferring said image printed substrate to at least one additional printing station in said continuous in-line process; and

printing additional images on the reverse side of said printed substrate in an offset lithographic process at said at least one additional printing station in said in-line process.

82. A method of combining lithography and flexographic printing in a continuous in-line process comprising the steps of:

(1) providing a plurality of successive printing stations for depositing a series of images on a substrate in said in-line continuous process;

(2) utilizing an anilox roller to transfer a liquid ink as one of said thin controlled layers to a flexographic plate image at at least one of said printing stations;

(3) printing said liquid ink from said flexographic plate image to one side of a substrate;

(4) transferring said printed substrate with said liquid ink image to a subsequent printing station in said in-line printing process;

(5) repeating steps (2)-(4) at subsequent printing stations in said in-line process to achieve a desired opacity ink image on the one side of said substrate; and

(6) printing an ink pattern on the reverse side of said substrate using an offset lithographic process.

83. A method as in claim 82 further including the step of additionally printing ink images over said liquid ink image on said substrate at subsequent ones of said printing stations in said in-line process.

84. A method as in claim 83 wherein said liquid ink is an opaque white color.

85. A method of combining offset lithography and flexography using a plurality of successive printing stations in a continuous in-line process, at least one of said stations comprising a flexographic printing station for printing an image on said substrate using a flexographic process:

(1) printing an image at one or more of said printing stations on a substrate using an offset lithographic process;

(2) transferring said image printed substrate to an additional and flexographic printing station and printing at said flexographic and additional printing station a coating on all or part of said image on said substrate;

(3) transferring said substrate to one or more additional printing stations for printing the reverse side of the said substrate; and

(4) printing an image on said reverse side of said substrate at one of such one or more printing stations using an offset lithographic process in the continuous in-line process.

86. Apparatus for a combined offset lithographic and flexographic printing process comprising:

(1) a substrate;

(2) a plurality of successive printing stations for depositing a series of images selected from a group consisting of lithographic and flexographic inks, coatings and slurries on one or both sides of a substrate in a continuous in-line process;

(3) at least one of said stations comprising a flexographic printing station for printing an image on said substrate using a flexographic process;

(4) at least one of said successive printing stations being an offset lithographic printing station whereby said offset lithographic printing station is used to deposit one of said lithographic materials on either side of the said substrate in the continuous in-line process;

87. Apparatus for a combined offset lithographic/flexographic printing process comprising:

a plurality of successive printing stations for printing images on a substrate in a continuous in-line process, said printing stations including both offset lithographic and flexographic printing stations for depositing lithographic inks, and one or more flexographic inks, coatings and slurries on said substrate, whereby said lithographic inks, and one or more flexographic inks, coatings and slurries may be printed successively on one or both sides of said substrate in the continuous in-line process.

Add C1




FIG. 2




FIG. 3


Robert Hardy Falk

Registration No. 27,877

A Texas Limited Liability Partnership

Dallas, Texas 75201

Facsimile: (214) 969-5941